

1500W Modified Sine Wave Inverter

KS1500M

| | | |
|---------|-----------------------|---|
| OUTPUT | Rated power | 1500W |
| | Surge power | 3000W(few seconds) |
| | Input voltage | DC 12V/24V/48V |
| | Output voltage | AC 110V/230V |
| | Output frequency | 50/60HZ |
| | No load current draws | <0.45A |
| | Output wave form | Modified sine wave |
| | USB port | 5V,2.1A |
| INPUT | Protection function | over temperature,over load, short circuit,,earth leakage |
| | Efficiency | More than 85% |
| | Protection function | Over voltage,reverse polarity Bat.low voltage alarm&shut down, |
| | Battery type | Open&sealed lead acid battery |
| | Remote control | Optional |
| | Cooling fan | By load and temperature control |
| | Product dimension | 250×220×90MM (L×W×H) |
| | Product Net weight | 4.0KG |
| | Certification | CE-EMC/LVD,RoHS |
| | Case color | Optional,default color is blue |
| | Accessories | Replaceable fuse+instruction book+connection wire |
| Packing | | Poly bag+EPE+inner box+carton |
| | | 1pc/inner box,2boxes/CTN |
| | | CTN dimension(CM):43×32×36CM (L×W×H) |
| | | N.W./G.W./CTN:8.0/9.7KG |

